

PhotoTex™

Versions & Sizes – Page 1 of 2

Aqueous, UV & Latex Inks.

Original

Translucent with 70% Opacity

Single print installs, elevator doors, events, promotions, windows & can be back lit.

Roll Sizes: 17", 24", 36", 42", 50", 54" & 60" x 100ft. & 54" x 150ft. (sheets also in stock)

Original - High Tack (EX)

Same as Original but 50% stronger tack.

Great for harder to stick to surfaces, events, texture walls, Low/ No VOC and eggshells paints, but still removable.

Roll Size: 42" x 100ft. roll.

(OPA) Opaque/Block-Out

20% stronger than the Original & 99% Opaque/block-out

Murals, Wallpaper & Cut-Outs. Hides overlapping panels.

Sticks on Low/No VOC & Eggshell paints along with semi-texture walls

Roll Sizes: 42", 54", 60" x 100ft. and 27"x150ft.

- 300ft rolls can be made upon special request.
- Always allow 30 days for newly painted walls to outgas before installing and ONLY use a warm damp rag to clean surfaces.
- Use a squeegee for all installs especially with Opaque.
- Do not use opaque on glass or steel.

Please e-mail me with any questions. walterjr@phototextgroup.com or for a sample request.

www.phototextgroup.com for features, benefits and technical information.

PhotoTex™

Versions & Sizes – Page 2 of 2

Solvent/Eco-Solvent & UV inks.

Original (S):

Translucent with 70% Opacity

Single print installs, elevator doors, doors, events, promotions, windows & can be back lit.

Rolls Sizes: 30", 42", 50", 54", & 60" x 100ft. & 54" x 150ft. (sheets also in stock)

Original - High Tack (EXS):

Same as Original, but 50% stronger tack.

Great for harder to stick to surfaces, events, texture walls, Low/No VOC and eggshells paints, but still removable.

Roll Size: 54" x 100ft. roll.

(OPAS) Opaque/Block-Out:

20% stronger tack than the Original & 99% Opaque/block-out.

Murals, Wallpaper & Cut-Outs. Hides overlapping panels

Sticks on Low/No VOC & Eggshell paints along with semi-texture walls

Roll Sizes: 30", 42", 50, 54" & 60" x 100ft.

- 300ft rolls can be made upon special request.
- Suggest liquid lamination for outdoors when using all (S) solvent inks.
- Always allow 30 days for newly painted walls to outgas before installing and ONLY use a warm damp rag to clean surfaces.
- Use a squeegee for all installs especially with Opaque.
- Do not use opaque on glass or steel.

Please e-mail me with any questions. walterjr@phototexgroup.com or for a sample request.
www.phototexgroup.com for features, benefits and technical information.